

Frost Fighter 2812 / 2824 ThermaSync Defroster Controls





12 / 24 Volt Defroster Controls

Defroster controls with smarts

New ThermaSync® Defroster Controls are the perfect companion to Clear View II and other defrosters.

All four models feature a remote defroster switch with red indicator light and automatic shut off timing.

The 2712 and 2724 controls provide simple automatic ten minute timing. The 2812 and 2824 defroster controls feature adjustable automatic shut off timing, power modulation and can be connected in a network to control multiple defrosters with a single switch.

2812 - 2824 ThermaSync Controls

ThermaSync controls are an ideal for vehicles which lack defroster circuitry or as a replacement to existing controls.

ThermaSync can run a wide variety of other heating devices including heated mirrors.

Adjustable Automatic Shutoff

ThermaSync controls automatically shut off in the standard ten minutes. Pressing the defrost symbol on the remote switch turns the defroster on. The defroster stays on until the switch is pressed again or the control times out.

The control can be set to time out at intervals from 10 to 160 minutes or can be left on indefinitely depending on the internal jumper settings.

Power Modulation

ThermaSync controls can modulate power to the defroster from 3% up to 100%. This feature allows for hundreds of new Clear View II defroster sizes to fit almost any window. Controls are configured at the factory to deliver full power. Do not change power modulation without calling the factory for technical assistance.

See the following page for more on power modulation.

Voltage Options

ThermaSync defroster controls and Clear View II defrosters are available in 12 and 24 volt.

SwitchBoss Network

A single switch can activate several defrosters using Switch Boss. This network control is good for equipment cabs and other applications that require several defrosters to be activated from a single switch.

Mounting Options

The ThermaSync control can be secured out of sight under the dash while the defroster switch can be mounted remotely in dash. The installation pack includes an under dash switch mounting plate.

Page 1 of 2

© 2012 Planned Products LLC All rights Reserved Frost Fighter and ThermaSync are Registered Trademarks of Planned Products LLC



ThermaSync Timing Defroster Control and Switch

2812 - 2824 Technical Data

Voltage...... 12 or 24 Volt Current Rating 20 Amps Power Modulation 3, 6, 12, 25, 50, 100 % Connectors Provided with control Connections Power, Ground, Defroster On Timer 10 Minutes standard Timer Adjust. (min) 10, 20, 40, 80, 160, Manual Switch Light Red LED Switch Flat Cable 34 inches long Symbol...... Defroster Housing ABS plastic Activation One Touch Multi-Control...... Yes with SwitchBoss Off during cycle? Yes Switch Size 1.5 in. x 1 in. x 1/4 deep Control Size 2.20 in x 1.35 in x 1.05 in Color Black



Planned Products LLC 4699 Nautilus Court S. Suite 201

Boulder, CO 80301

Tel: (303) 682-0274
Fax: (303) 682-0678
email: info1@frostfighter.com
Web: www.frostfighter.com

2812 / 2824 Frost Fighter ThermaSync Defroster Controls



12 / 24 Volt Controls

(H) Defroster (-) Ground (+) Positive

ThermaSync Defroster Control





Many defrosters, one switch SwitchBoss Network control

ThermaSync Installation Pack



Planned Products LLC 4699 Nautilus Court S.

Suite 201 Boulder, CO 80301

(303) 682-0274 Tel: Fax: (303) 682-0678 info1@frostfighter.com email: www.frostfighter.com Weh:

More Options, Less Hassle

New ThermaSync® defroster controls are easy to wire, configure and operate.

Connectors

The back of the control has three connectors. These are positive, ground and defroster each a different size to discourage cross wiring. Connectors are supplied with every control.

The optional 2728 Installation Pack includes a labeled and color coded wire harness with fast-on connectors.

Defroster Switch

The defroster switch features an easy push button, standard defroster symbol and red indicator light. The ThermaSync control connects to the switch with 34 inch (91) flat cable. The switch can be positioned in the dash while the control can be tucked neatly away under dash.

Installation Pack



The 2728 Installation Pack makes it easy to get install ThermaSync defroster controls. The wire harness includes color coded connectors, fuse and fuse holder, power tap, under dash switch mounting bracket, mounting screws and wire ties for a perfect installation.

Color coded connectors Instructions

All defroster controls come with fully illustrated step-by-step instructions.

Clear View II Defrosters

Now available in hundreds of sizes in 12 and 24 volt Clear View II defrosters reliably melt snow and ice in minutes.

Each defroster has a specific power modulation requirement which must be matched by the ThermaSync control. Only 2812 and 2824 controls feature power modulation.

ThermaSync Defroster Controls			
2712	Control and switch	12 Volt RELAY	\$33.95
2812	Control and switch	12 Volt MOSFET	\$39.95
2724	Control and switch	24 Volt RELAY	\$43.95
2824	Control and switch	24 Volt MOSFET	\$49.95
2728	Installation Pack	12/24	\$28.95